

COBRA WIRE & CABLE BOAT CABLE® UL 1426 - Round

Cobra Part Number	Size	Conductors	Stranding	Insulation	Nominal OD	Cable Weight
	AWG				IN	
B8W16T-XX	16	2	26 X 30	0.030	.313	49
B8G16T-XX	16	2	26 X 30	0.030	.313	49
B8W16T-XX	16	3	26 X 30	0.030	.333	64
B8G16T-XX	16	3	26 X 30	0.030	.333	64
B8W16T-XX	16	4	26 X 30	0.030	.366	80
B8G16T-XX	16	4	26 X 30	0.030	.366	80
B8W16T-XX	16	5	26 X 30	0.030	.399	95
B8G16T-XX	16	5	26 X 30	0.030	.399	95
B8W16T-XX	16	6	26 X 30	0.030	.436	111
B8G16T-XX	16	6	26 X 30	0.030	.436	111
B8W14T-XX	14	2	41 X 30	0.030	.349	66
B8G14T-XX	14	2	41 X 30	0.030	.349	66
B8W14T-XX	14	3	41 X 30	0.030	.393	89
B8G14T-XX	14	3	41 X 30	0.030	.393	89
B8W14T-XX	14	4	41 X 30	0.030	.408	109
B8G14T-XX	14	4	41 X 30	0.030	.408	109
B8W14T-XX	14	5	41 X 30	0.030	.458	132
B8G14T-XX	14	5	41 X 30	0.030	.458	132
B8W14T-XX	14	6	41 X 30	0.030	.488	153
B8G14T-XX	14	6	41 X 30	0.030	.488	153
B8G12T-XX	12	2	65 X 30	0.030	.409	98
B8W12T-XX	12	2	65 X 30	0.030	.409	98
B8G12T-XX	12	3	65 X 30	0.030	.434	128
B8W12T-XX	12	3	65 X 30	0.030	.434	128
B8G12T-XX	12	4	65 X 30	0.030	.476	160
B8W12T-XX	12	4	65 X 30	0.030	.476	160
B8W12T-XX	12	5	65 X 30	0.030	.523	191
B8G12T-XX	12	5	65 X 30	0.030	.523	191
B8W10T-XX	10	2	105 X 30	0.030	.467	138
B8G10T-XX	10	2	105 X 30	0.030	.467	138
B8G10T-XX	10	3	105 X 30	0.030	.497	184
B8W10T-XX	10	3	105 X 30	0.030	.497	184
B8G10T-XX	10	4	105 X 30	0.030	.555	232
B8W10T-XX	10	4	105 X 30	0.030	.555	232
B8W10T-XX	10	5	105 X 30	0.030	.616	496
B8G10T-XX	10	5	105 X 30	0.030	.616	496
B8G8T-XX	8	4	133 X 28	0.045	.768	386
B8W8T-XX	8	4	133 X 28	0.045	.768	386
B8G6T-XX	6	4	266 X 30	0.060	.975	700

W=White, G=Gray