



UP10-MS/XC Stainless Steel Pump with Mechanical Seal, PEEK gears 4.75 gpm

Quick Overview

Self-priming electric pumps with compact mechanical seal and helical gears in PEEK. The drive shaft is made of AISI316, with a stainless steel body and fittings. Mechanical seal with EPDM or FKM components. The enhanced motor is designed for continuous use under pressure.

Part n.	Name	Voltage (V)	MAX Amperage (A)	Fuse (A)	MAX Flow rate (gpm)	Self-priming (ft)	Pressure (psi)	O-Ring	Seal	Hz	Ports (B SPP)	Hose (in)	IP Protection	Motor power (W)	Weight (lb)
1E440112	UP10-MS/XC	12	26	35	4.8	9.8	116	EPDM	EPDM	DC	3/8"	0.5	67	360 W	8.4
1E440113	UP10-MS/XC	24	13	20	4.8	9.8	116	EPDM	EPDM	DC	3/8"	0.5	67	360 W	8.4
1E440116	UP10-MS/XC	48	8	15	4.8	9.8	116	EPDM	EPDM	DC	3/8"	0.5	67	360 W	8.4
1F440112	UP10-MS/XC	12	26	35	4.8	9.8	116	FKM	FKM	DC	3/8"	0.5	67	360 W	8.4
1F440113	UP10-MS/XC	24	13	20	4.8	9.8	116	FKM	FKM	DC	3/8"	0.5	67	360 W	8.4

